

# Technical Sheet

## Washing Rack Conveyor

### Mod. A-2700-T



### Characteristics

|                                |                                 |
|--------------------------------|---------------------------------|
| Dimensions                     | 2700 x 830 x 1715 mm.           |
| Speeds                         | 2                               |
| Production Racks / Dishes hour | 85- 170 / 1360 - 2720           |
| Usable washing height          | 420 mm.                         |
| Water consumption hour         | 250 / 280 l/h.                  |
| Water connexion                | 3/4"                            |
| Water inlet pressure           | 2 - 4 bars / 200 - 400 Kpa.     |
| Drainage                       | ø 50 mm.                        |
| Nº Upper pre-washing arms      | 3                               |
| Nº Lower pre-washing arms      | 3                               |
| Nº Upper pre-washing suppliers | 18                              |
| Nº Lower pre-washing suppliers | 18                              |
| Pre-washing tank capacity      | 50 l.                           |
| Nº Upper washing arms          | 4                               |
| Nº Lower washing arms          | 4                               |
| Nº Upper washing suppliers     | 24                              |
| Nº Lower washing suppliers     | 24                              |
| Washing tank capacity          | 60 l.                           |
| Boiler capacity                | 2 x 11,5 l.                     |
| Pre-washing pump power         | 2 Kw.                           |
| Washing pump power             | 2 kw.                           |
| Tank heating element           | 18 kw.                          |
| Drying heating element         | 12 kw. (18 kw.* optional)       |
| Boiler heating element         | 24 kw. (18 kw.*)                |
| Total power                    | 50 Kw. ( 44 kw.*)               |
| Voltage                        | 230 - 400V. / III / 50 - 60 Hz. |

### Modules

|                                      |          |
|--------------------------------------|----------|
| Entry<br>200 mm                      | ●        |
| Prewash<br>880 mm                    | ●        |
| Wash with<br>Double Rinse<br>1120 mm | ●        |
| Exit<br>500 mm                       | ●        |
| CV + R<br>(+ 150 mm<br>height)       | Optional |
| SWF<br>(+ 300 mm<br>entry)           | Optional |
| Enhanced<br>ECO-Rinse                | -        |
| Drying                               | ●        |

### Baskets provision

3 Dishes  
2 Universal  
16 Cutlery

\* In case of hot water supply o EPS Advance (CV+R) , possibility of reducing power by commuting elements.

